



NOTES:

- 1) ALL DIMENSIONS GIVEN IN INCHES (MM) AND ARE FOR REFERENCE ONLY.
- 2) WHERE EXTREME OR UNUSUAL CONDITIONS EXIST, OR SPECIAL MAINFRAME LENGTHS ARE REQUIRED. CONSULT MARTIN ENGINEERING FOR ASSISTANCE.
- 3) TENSIONER MAY BE BOLTED OR WELDED IN PLACE. MARTIN ENGINEERING RECOMMENDS BOLTING WHEN APPLICABLE FOR EASIER MAINTENANCE AND ACCESSIBILITY.
- 4) REFER TO OPERATOR'S MANUALS OF SPECIFIC CLEANERS FOR INSTALLATION DETAILS.
- 5) AFTER INSTALLATION OF TENSIONER, EXCESS LENGTH OF HANGER MOUNT CAN BE CUT OFF.
- 6) HANGER MOUNT MUST BE INSTALLED PERPENDICULAR TO THE BELTLINE.

© Copyright 2002 Martin Engineering. All rights reserved. Covered by U.S. and foreign patents pending and issued. ® and ™ indicate trademarks of Martin Engineering.

MARTIN ENGINEERING
NEPONSET ILLINOIS USA

TITLE	QC#1 HD PRE-CLEANER WITH TWIST TENSIONER & DUAL QC#2 SECONDARY TENSIONERS	DRAWN <i>MJT</i>
		DATE 08/05/02
		CHECKED
		ENG. <i>JCB</i>
		DATE 08/06/02
		APPROVED <i>JCB</i>
		DATE 08/06/02
SALES DRAWING		SCALE 1/4

NO.	DESCRIPTION	ECN	DATE	BY
A	UPDATE QC#2 PICTORIALY/ADD DIM 2 X Ø.625 & 2.00 MIN/4.00 MAX (2)/ADD CUTOUT DETAIL/CHG DIM FROM 7.38 TO 7.43/CHG P/N 27658-0912 TO CYAR-0912	12408	10/04/11	MJB
REVISION				